



1. RX50XF DESIGNED MIX TO BS 8500:2:2006 CEMENT CONTENT 340 kg/m<sup>3</sup> W/C RATIO BY WEIGHT 0.45. MAX. AGGREGATE SIZE 20mm CONSISTENCE CLASS OF S3. BRUSH TEXTURED FINISH TO CLAUSE 1026 & TABLE 10/8 DOT SPEC.
2. B385, LONG MESH FABRIC REINFORCEMENT, COVER 60mm, TRAVERSE OVERLAP[ MIN. 300mm FABRIC TO TERMINATE WITHIN 60± 20mm OF JOINT LINE. MAIN BARS TO RUN PARALLEL TO LONGITUDINAL JOINTS.
3. WATERPROOF MEMBRANE MIN. 250 MICRONS THICK, MIN. 300mm LAP.
4. JOINT SEALANT SERVICED PARASEAL, OR EQUIVALENT APPROVED.
5. 225mm THICK SLAB - ROAD.  
225mm THICK SLAB - SERVICE YARD.  
200mm THICK SLAB - INTERNAL.
6. 300mm SUB-BASE OF TYPE 1 GRANULAR MATERIAL TO CLAUSE 803 OF DoT SPEC.
7. 450mm THICK GRANULAR MATERIAL TYPE 6F1 TO DoT SPECIFICATION. GRANULAR MATERIAL LAID IN ACCORDANCE WITH CLAUSE 802 DoT SPECIFICATION CLAUSE 612.

THIS DRAWING IS COPYRIGHT © CAMBRIA CONSULTING LTD.

DO NOT SCALE FROM THIS DRAWING.

CONTRACTORS MUST CHECK ALL DIMENSIONS ON SITE. ONLY FIGURED DIMENSIONS ARE TO BE WORKED FROM. DISCREPANCIES MUST BE REPORTED IMMEDIATELY TO CAMBRIA CONSULTING LIMITED BEFORE PROCEEDING.

THE CONTRACTOR IS TO REFER TO THE SPECIFICATION, FULL SCHEDULE OF RESIDUAL RISKS IN THE CONTRACT DOCUMENTATION AND ALSO TO INFORMATION FROM OTHER DESIGNERS, IN PARTICULAR THE M&E CONSULTANT REGARDING EXISTING LIVE SERVICES.



THIS SYMBOL IS USED TO HIGHLIGHT INSTANCES OF RISK WITHIN THE CONSTRUCTION PROCESS.

ALWAYS CHECK FOR LATER REVISIONS OF THIS DRAWING.

A	FIRST ISSUE FOR COMMENT	MD	WJ
		30/09/13	

Client:

EXPRESS PARK BUXTON LTD.

Project:

EXPRESS PARK BUXTON

Drawing Title:

SLAB DETAIL

Project No.:	Drawing No.:	Revision:
CC1147	114	A
Status:	Scale:	
PRELIMINARY	AS SHOWN @ A3	

**CAMBRIA**  
Constructive Thinking

Civil & Structural Engineers  
Cambria House  
16 Plas St. Pol de Leon  
Penarth Marina  
Cardiff, CF64 1TR

T 029 2009 3333  
E admin@cambria.co.uk  
W www.cambria.co.uk  
@cambriauk  
uk.linkedin.com/in/cambriauk