

10/04/2015

7 APR 2015

LOCAL COUNCIL

20mm THICK FLEX CELL (OR SIMILAR APPROVED)  
COMPRESSIBLE BOARD WITH 20mm X 20mm POLYSULPHIDE  
WATERPROOF SEALANT AT TOP

75mm SCF EED.

150mm (5) ROUND BRICKING SLAB

1200 GAUGE VISQUEEN DPM  
LAPPED UP SLAB EDGE

NOMINAL SAND  
BLINDING

150mm TYPE 1 MOT WEIL  
(COMPACTED) SUB BASE

300

600

100  
100  
100

DPC

EXISTING  
FACING BRICK TO MATCH

GROUND LEVEL

WEAK MIX CAVITY  
FILL UP TO  
GROUND LEVEL

MIN 900MM

BOTTOM OF FOOTING TO BE MINIMUM 900MM  
FROM GROUND FLOOR LEVEL.  
LABC MAY REQUEST FURTHER FOUNDATION  
EXCAVATION THIS IS TO PERFORMED UNTIL THE  
GROUND IS DEEMED SUFFICIENT & TO THE  
SATISFACTION OF LABC AND REGULATION 4.1/A2.

TYPICAL SECTION THROUGH  
PROPOSED FOUNDATION/FLOOR