

Contractor to accurately measure dimensions & levels on site in order to achieve a satisfactory fit of wall, gates & stepping prior to construction.

Wall to be constructed from natural stone to match buildings, eg High Peak Dale Gritstone. All stone to be compliant with BS EN 12440: 2008 & BS EN 771-6: 2011 Unit sizes - Main wall Face LxHxD: 300x65x100mm;225x140x100mm;225x65x100mm. End of wall: - 300x65x100mm; 225x140x210mm; 225x140x100mm Coping: 200x100x380mm


Bond: Alternate Couse Bonded - 140 mm and 65mm

Natural Mortar to match building.

Cavity between faces to be filled with small gauge stone rubble and cement mix. Wall faces to be tied with stainless steel ties.

Foundation to be 450mm below ground and to Engineers specification. Walling material to travel to foundation below ground or substituted with concrete brick or Engineering brick. Only natural stone wall material to be visible above ground as illustrated in drawing.

All work to be carried out by competent stone mason or experienced natural stone walling contractor.





PGLA Ltd Landscape Architects 23 New Mount Street Manchester M4 4DE

t: 0161 212 1131 e: info@pgla.co.uk w: www.pgla.co.uk

Client

Mr T Bagshawe

Batham Gate Road, Peak Dale

1.8m Natural Stone Wall

1:20 at A3

PGG

April 15

Job number BAT1311

Drawing number L006

Revision