





Cromwell Split Face, Buff, Elland

Marshall's new and improved finer faced Cromwell Walling is manufactured using Yorkstone aggregates to closely replicate the visual and textured characteristics of natural stone.

Cromwell Walling successfully achieves the visual impact of random and variably sized natural stone walling, whilst providing the consistency of modern production methods allowing quick construction times.

Cromwell is available in three distinct styles:

■ **Cromwell Pitched Face Walling**

Cromwell Pitched Face Walling has a rough effect and each block displays a distinctive raised centre. Cromwell Pitched Face walling is a versatile reconstructed walling, suitable for both commercial applications and high quality housing.

■ **Cromwell Split Face Walling**

For applications where a flatter, less prominent texture than a pitched face is required, Cromwell Split Face Walling provides a striking alternative, ideal for high profile commercial projects.

■ **Cromwell Rustic Walling**

Cromwell Rustic Walling gives finished walling a rounded, softer and less defined finish, replicating the appearance of older, reclaimed natural stone walling.

Cromwell Pitched Face, Split Faced and Rustic Walling is supplied in four colours:

■ **Yorkstone**

Reflecting the characteristics and charm of original sandstone walling

■ **Weathered**

Creating the timeless appeal of older, more mature stone walling

■ **Brown**

A subtle shade to provide variety and choice

■ **Ash**

Where a cooler contemporary colour variant is preferred.



Cromwell Pitched Face, Weathered, Queensbury

Cromwell Fine Face Walling



Cromwell Pitched, Yorkstone



Cromwell Split Face, Yorkstone



Cromwell Rustic, Yorkstone



Cromwell Pitched, Weathered



Cromwell Split Face, Weathered



Cromwell Rustic, Weathered



Cromwell Pitched, Brown



Cromwell Split Face, Brown



Cromwell Rustic, Brown



Cromwell Pitched, Ash



Cromwell Split Face, Ash



Cromwell Rustic, Ash

Cromwell Performance

■ Conforms to BS EN 7710-5:2003

■ Exceptionally low water absorption properties

A hydraulically pressed unit results in low water absorption which guarantees a long-term, high quality face appearance. This also ensures the visual appearance is not degraded over time by frost attack or ingress of surface grime

■ High crushing strength and density

Suitable for both load bearing and non-load bearing applications

Cromwell Range and Variety

■ Stones are manufactured in a range of course heights and length options

The wide variety of course heights and stone lengths offered ensure that the finished walling has all the characteristics of random length natural stone walling.

Cromwell Pitched Face	Stone Size Height (course) x Length (mm)	Stone Weight (kg)	Stones per Pack (number)	Laid Number of Stones (per m ²)	Area Total Pack (m ²)	Course Length Total Pack (approx lin m)*	Yorkstone Pitched Face Ref No.	Weathered Pitched Face Ref No.	Brown Pitched Face Ref No.	Ash Pitched Face Ref No.
	65 x 220	3.4	358	57.97	6.18	82.34	WA090100F	CKWA095100F	CKWA092100F	WA0905000
	140 x 300	9.8	135	21.51	6.28	41.85	WA090150F	CKWA095150F	CKWA092150F	WA0905200
	140 x 365	11.9	100	17.78	5.62	37.50	WA090080F	CKWA095080F	CKWA092080F	WA0905300
	140 x 440	14.1	90	14.81	6.08	40.50	WA090090F	CKWA095090F	CKWA092090F	WA0905400

Cromwell Split Face	Stone Size Height (course) x Length (mm)	Stone Weight (kg)	Stones per Pack (number)	Laid Number of Stones (per m ²)*	Area Total Pack (m ²)*	Course Length Total Pack (approx lin m)*	Yorkstone Split Face (Ref No.)	Weathered Split Face (Ref No.)	Brown Split Face (Ref No.)	Ash Split Face (Ref No.)
	65 x 220	3.4	358	57.97	6.18	82.34	WA070100F	CKWA075005F	CKWA072005F	WA0752000
	140 x 300	9.8	135	21.51	6.28	41.85	WA070150F	CKWA045150F	CKWA072150F	WA0752100
	140 x 365	11.9	100	17.78	5.62	37.50	WA075080F	CKWA072080F	CKWA092080F	WA0752200
	140 x 440	14.1	90	14.81	6.08	40.50	WA070090F	CKWA075090F	CKWA072090F	WA0752300

Cromwell Rustic	Stone Size Height (course) x Length (mm)	Stone Weight (kg)	Stones per Pack (number)	Laid Number of Stones (per m ²)*	Area Total Pack (m ²)*	Course Length Total Pack (approx lin m)*	Yorkstone Rustic (Ref No.)	Weathered Rustic (Ref No.)	Brown Rustic (Ref No.)	Ash Rustic (Ref No.)
	65 x 220	3.3	320	57.97	5.52	73.60	WA096010F	CKWA098010F	CKWA097010F	WA0990100
	140 x 300	9.8	120	21.51	5.58	37.20	WA096070F	CKWA098070F	CKWA097070F	WA0990300
	140 x 365	11.8	90	17.78	5.06	33.75	WA096080F	CKWA098080F	CKWA097080F	WA0990400
	140 x 440	13.2	80	14.81	5.40	36.00	WA096090F	CKWA098090F	CKWA097090F	WA0990500

The nominal bed size of all stones is 100mm. The nominal work size of stones can be assumed to be 10mm larger than the stone size shown above.

*Assumes a nominal 10mm joint. All items available ex-stock.