

OLD CLUB HOUSE

1 WATER STREET

BUXTON

SK17 6XN

Lighting Assessment

ITEMA 01A & 01B (Qty 2) PICTORIAL

Double sided pictorial sign.

Featuring:

- Standard 900 mm GK Illuminated header finished RAL 9005 / crown finished Lechler MR3310.
- 8 mm acrylic letters finished NCS N9145 / 5 mm acrylic letters finished Lechler MR3310.
- Mild steel gibbet finished RAL 9005.
- 2 mm Aluminium panel finished F&B Stiffkey Blue.
- 32 mm Bullnose trim finished F&B Stiffkey Blue.
- Signwritten text in F&B Tallow.
- 3D built up pictorial content.
- 2No. Slimline LED trough lights.
- Warm white illumination.

The pictorial panel will be illuminated by an LED trough light fitted with a shield to prevent light spillage and with warm white illumination to give a softer light. These would replace the existing pictorial and lighting

ITEMS 02A & 02B (Qty 2) LETTERS

Set of individual letters.

Featuring:

19 mm Foamex letters finished F&B Tallow. Brass locators.

Pencil LED trough light. Warm white illumination.

The proposed lighting would replace the existing trough lights for slimmer LED warm white illuminated fittings.

ITEM 03 (Qty 1) LETTERS

Set of individual letters.

Featuring:

19 mm Foamex letters finished F&B Tallow. Brass locators.

Pencil LED trough light. Warm white illumination.

The proposed lighting would replace the existing trough lights for slimmer LED warm white illuminated fittings.

ITEM 06 (Qty 15) FLOODS

50W LED Slimline floodlight.

Featuring:

- Warm white illumination.

The proposed floods would replace existing floodlights around the building. These would be energy efficient LED lights with warm white illumination and would be angle down onto the building to prevent light spillage

ITEM 09 (Qty 1) LANTERN

Brass Warwick C lantern.

Featuring:

- Spreader bracket finished Black.
- Name in Black to 3No. sides.
- Warm white illumination.

The proposed lantern would be located over the main entrance to give soft light to the entrance for the safety of customers entering and leaving the building

Impact

The proposed lighting would not exceed 250cdl/m² and be fitted with shields to prevent light spillage They would have warm white bulbs to give a softer light. Great care would be taken to angle the lighting to illuminate the signs/building only