



Windows and Door Specifications for Hyde Bank Court

1	ECO Slide Vertical Slider(WER:1.4 U-Valu)	
O/A Sizes 1100mm x 1200mm (ECO V/S)	Specification	
 Cill Horn : 0mm	Colour	White
	Cill colour	White
	Cill	4005 152mm Cill
	Add-on (Head)	-
	Add-on (Cill)	-
	Add-on (Left jamb)	-
	Add-on (Right jamb)	-
	Ventilator (Head)	10000 Eco Vent
	Ventilator (Sash)	-
	VS Sash Horns	Run Through Horns
	VS Hardware Colour	Satin Chrome
	VS Travel Restrictor	Travel Restrictor Required
	VS Sash Locks	2 x Cam Lock
	VS Keeps	Cam Lock Keep
	VS Top Sash	2 x Pole Eye Top Sash
	VS Bottom Sash	2 x Sash Lift
	VS Outside D Handle	-
	Glazing thickness	24mm
	VS Tilt Knobs	Tilt Knobs Required

Glazing Details & Apertures


4-16-4 Softcoat / Low Iron Tuff : 16mm Warm Edge

A1 A6

O/A Sizes 950mm x 1400mm (ECO V/S)	Specification	
 Cill Horn : 0mm	Colour	White
	Cill colour	White
	Cill	4005 152mm Cill
	Add-on (Head)	-
	Add-on (Cill)	-
	Add-on (Left jamb)	-
	Add-on (Right jamb)	-
	Ventilator (Head)	7500 Eco Vent
	Ventilator (Sash)	-
	VS Sash Horns	Run Through Horns
	VS Hardware Colour	Satin Chrome
	VS Travel Restrictor	Travel Restrictor Required
	VS Sash Locks	2 x Cam Lock
	VS Keeps	Cam Lock Keep
	VS Top Sash	2 x Pole Eye Top Sash
	VS Bottom Sash	2 x Sash Lift
	VS Outside D Handle	-
	Glazing thickness	24mm
	VS Tilt Knobs	Tilt Knobs Required


Glazing Details & Apertures

4-16-4 Softcoat / Low Iron Tuff : 16mm Warm Edge

O/A Sizes 1100mm x 1400mm (ECO V/S)	Specification	
 Cill Horn : 0mm	Colour	White
	Cill colour	White
	Cill	4005 152mm Cill
	Add-on (Head)	-
	Add-on (Cill)	-
	Add-on (Left jamb)	-
	Add-on (Right jamb)	-
	Ventilator (Head)	10000 Eco Vent
	Ventilator (Sash)	-
	VS Sash Horns	Run Through Horns
	VS Hardware Colour	Satin Chrome
	VS Travel Restrictor	Travel Restrictor Required
	VS Sash Locks	2 x Cam Lock
	VS Keeps	Cam Lock Keep
	VS Top Sash	2 x Pole Eye Top Sash
	VS Bottom Sash	2 x Sash Lift
	VS Outside D Handle	-
	Glazing thickness	24mm
	VS Tilt Knobs	Tilt Knobs Required

Glazing Details & Apertures

4-16-4 Softcoat / Low Iron Tuff : 16mm Warm Edge

1	Linair Sculpt Composite Door	Specification	
O/A Sizes 1000mm x 2410 / 2100mm (Sty)		Specification	
		Frame (Head)	LWS018 67mm Composite Fr
		Frame (Cill)	LWS018 67mm Composite Fr
		Frame (Left jamb)	LWS018 67mm Composite Fr
		Frame (Right jamb)	LWS018 67mm Composite Fr
		Frame (AFT)	LWS018 67mm Composite Fr
		Threshold	No threshold
		Add-on (Cill)	No add-on
		Colour	White
		Cill colour	White
		Handle	No Handle (No Prep)
		Cill	LSL150 150mm Cill
		Drainage	Concealed/Base
		Ventilator (Sash)	No ventilator
		Ventilator (Glass)	No ventilator
		Ventilator (Frame)	No ventilator
		Bead type	LSW041 Composite Bead
		Door lock	Yale Keywind Heritage Comp
		Cylinder	Standard Cylinder
		Open in/out	Open in
		Door Numerals	2 x Gold Numerals
		Door Letterplate	Gold Letterplate (Mid)
		Shape Surcharge	D2
		Keyed Alike	No